



Super Drive Professional Woodscrews

- Industry standard pozi recessed head
- Ribbed double countersunk to give a flush finish
- Hardened steel for high torque loads
- Zinc & yellow passivated coating ensures total corrosion resistance
- Fully threaded under 80mm for maximum holding power
- 40° thread angle to give maximum pull out resistance
- Knurled thread increases drive speed by up to 20%
- Type 17 point for easier starting in all timbers



Code	Screw Gauge	Length	Finish	Box Quantity	Carton Quantity
SPD30012	3.0mm	12mm	Zinc & Yellow	200	18000
SPD30020	3.0mm	20mm	Zinc & Yellow	200	18000
SPD30025	3.0mm	25mm	Zinc & Yellow	200	10000
SPD35012	3.5mm	12mm	Zinc & Yellow	200	18000
SPD35016	3.5mm	16mm	Zinc & Yellow	200	18000
SPD35020	3.5mm	20mm	Zinc & Yellow	200	10000
SPD35025	3.5mm	25mm	Zinc & Yellow	200	8400
SPD35030	3.5mm	30mm	Zinc & Yellow	200	8400
SPD40020	4.0mm	20mm	Zinc & Yellow	200	8400
SPD40025	4.0mm	25mm	Zinc & Yellow	200	8400
SPD40030	4.0mm	30mm	Zinc & Yellow	200	4800
SPD40040	4.0mm	40mm	Zinc & Yellow	200	4800
SPD40045	4.0mm	45mm	Zinc & Yellow	200	4800
SPD40050	4.0mm	50mm	Zinc & Yellow	200	2600
SPD40060	4.0mm	60mm	Zinc & Yellow	200	2600
SPD40070	4.0mm	70mm	Zinc & Yellow	100	2400
SPD50030	5.0mm	30mm	Zinc & Yellow	200	4800
SPD50040	5.0mm	40mm	Zinc & Yellow	200	2600
SPD50050	5.0mm	50mm	Zinc & Yellow	200	2600
SPD50060	5.0mm	60mm	Zinc & Yellow	100	2400
SPD50070	5.0mm	70mm	Zinc & Yellow	100	2400
SPD50080	5.0mm	80mm	Zinc & Yellow	100	1300
SPD50090	5.0mm	90mm	Zinc & Yellow	100	1300
SPD50100	5.0mm	100mm	Zinc & Yellow	100	1300
SPD60050	6.0mm	50mm	Zinc & Yellow	100	2400
SPD60060	6.0mm	60mm	Zinc & Yellow	100	1300
SPD60070	6.0mm	70mm	Zinc & Yellow	100	1300
SPD60080	6.0mm	80mm	Zinc & Yellow	100	1300
SPD60090	6.0mm	90mm	Zinc & Yellow	100	1300
SPD60100	6.0mm	100mm	Zinc & Yellow	100	1300
SPD60120	6.0mm	120mm	Zinc & Yellow	50	600
SPD60130	6.0mm	130mm	Zinc & Yellow	50	600
SPD60150	6.0mm	150mm	Zinc & Yellow	50	600

**ALSO AVAILABLE
CLAM-PACKED**

