

sales@johngeorge.co.uk

Wholesale distributors to merchants

in the building, roofing, fencing and agricultural trades

Snowguard and Brackets Product

The snowguard system is designed to prevent the fall of snow and tiles from pitched roofs. The system is mainly used in domestic applications to protect conservatories and other damageable installations below the pitched roof, and in commercial surroundings to protect public areas from falling debris.

Information

Snowquard Panels

- Are manufactured from mild steel wire to a length of 2m
- Are available in heights of 150mm and 225mm
- Are hot dip galvanised after manufacture to give a long life finish

6.13mm Top Wire

2.31mm Mesh Wire

4.32mm Bottom Wire

Snowguard Brackets are available in 3 types. All are made from 4mm galvanised steel and hot dip galvanised after manufacture:

- Round Gutter (or Half Round) to fix guard in front of the gutter
- · Over Gutter to fix guard behind the gutter
- V-Shaped to fix to the top end of the rafter

Snowguard Code	Size	Bracket Code		
		Round Gutter	Over Gutter	V-Shaped
RSNG06	150mm x 2 Metre	RSNG06B	RSNG06OG	RSNG06V
RSNG09	225mm x 2 Metre	RSNG09B	RSNG09OG	RSNG09V

Fitting Instructions

All brackets have pre-drilled holes and should be fitted at regular 1 metre intervals.

The snowguard panel is fixed to - the roofside of the bracket using the hole at the top of the bracket using either galvanised tying wire or cable ties.

Round Gutter

to the soffit underneath the guttering using the two pre-drilled holes.

The bracket is fixed

Over **Gutter**

V-Shaped

Fitted directly onto the rafters where no gutter is used.

FAST:

Tel: 01268 663130 Fax: 01268 663131

WFST: Tel: 01275 335810 Fax: 01275 349203

CENTRAL: Tel: 0118 941 1234 Fax: 0118 945 1059